

The compact supply kits with controller are suitable for the diesel own consumption supply, measuring, and control for fleet vehicles.

**Composed of:**

- Chassis made of steel and stainless steel. Finished with brilliant epoxy paint with special interior and exterior treatment against corrosion. Weatherproof
- 4 m Ø19 or 25 mm (depending on the pump) double layer delivery hose with adapters in both ends

**Controller features:**

- The GK-7 controller is suitable for the supply control allowing its use only to authorized personnel.
- User and/or vehicle identification through codes and/or identification key
- Supply with or without litre preset.

**It controls:**

- supply hour and date
- Users: 60 or 130 (depending on the model)
- Vehicles
- Supplied litres
- Car mileage (or hours) and consumption
- Stock of the litres in the tank

The services are saved in memory and can be transferred to a computer through the following communication kits:

- via memory key (maximum 100 users)
- via USB/RS-485 cable
- via GSM modem
- via ETHERNET
- via ZIGBEE (wireless)

The query and configuration operation can be done from the computer through the GKSuite software or directly from the supply kit with the code or the identification key, being able to:

- Input or delete users and/or vehicles.
- Assign or change the codes or the identification keys of the users and/or vehicles.
- Calibrate the supply kit.
- Consult the done supplies.
- Consult and regularize the tank stock.
- Configure the communication and other options of the controller.
- Create and configure alarms.

The supply kits with GK-7Plus do not need the communication kit because they make the communications automatically, saving the data on the Internet. Access the supply kit and the data through the web site: [www.dieselplus.net](http://www.dieselplus.net) subject to the acquisition of a licence (page 43).



45-75  
l/min  
±0.5%

mm\* (approx.) 405 - 460  
kg\* (approx.) 22.5 - 32.5



Refer to Software - page 43-46

DESCRIPTION

CODE

COMPACT SUPPLY KITS WITH GK-7 CONTROLLER

Diesel	Voltage	Controller GK-7	Automatic nozzle	Flow l/min	
■ COMPACT 50K-60 230	230 VAC	●	PA-60	40-50	28540-CF00000
■ COMPACT 50K-60 12	12 VDC	●	PA-60	35-45	28580-CF00000
■ COMPACT 75K-60 230	230 VAC	●	PA-80	70-80	28640-CF00000
■ COMPACT 90K-60 12	12 VDC	●	PA-80	70-80	28590-CF00000
■ COMPACT 100K-60 230	230 VAC	●	PA-120	75-85	28650-CF00000

**CONFIGURATION:**

\*By default: 60-user/vehicle memory, identification key reader (IButton)

**USER/VEHICLE MEMORIES**

(●) 60-user/vehicle memory · 200 services

(+) 130-user/vehicle memory · 500 services\*

\*Communication with key maximum 100 users/vehicles and 200 services

**Optional:**

- GK-7 Identification key (pack of 10 units)
- Hexagonal pedestal base (height 1 m) (page 59)
- F1 " aluminium flange kit (special for COMPACT)

-  
FE007002

251201002  
800400015  
800003029



Pedestal base

F1 " aluminium flange kit



Identification keys



► For the PC connection