

RT 003 DHC

Ref.055346



Professional tester, easy to use, very fast and accurate

- √ Battery 6-12V
- ✓ Starter 12-24V
- ✓ Alternator circuit 12-24V









Testing the battery

Able to test 4 technologies of lead-acid batteries from 7 to 230Ah:

Open SLI or maintenance free batteries /GEL/AGM/SPIRAL/START&STOP

✓ Multi-standard

Norme SAE: from 40 to 2000 A Norme DIN: from 25 to 1300 A Norme IEC: from 30 to 1500 A Norme EN: from 40 to 2100 A

Norme JIS: Battery type number (Japan)

- Unique and patented tester thanks to its technology
 Of measur eof dynamic strength:
 - · Minimizes the battery discharge
 - Displays reliable and actual results, not distorbed by :
 - Surface charge

(usual necessary time before measure for stabilisation of the electrolyte and of the active materials)

- Auxiliary consumptions (lights, miscellaneous indicators...)
- Contact defects

(battery terminals/ lug oxydation, lugs not tightened...)

- ✓ Test :
 - Without disconnecting the battery from the vehicle
 - · On a separate battery
- ✓ The test can be done even on a highly discharged battery (from 1,5 V)
- Protected against polarity reversal
- ✓ **Instantaneous analysis** (within 2 seconds)

With digital display on a bright LCD screen :

- Battery voltage (1,5V ► 30V)
- Available starting power (actual or in %)
- State of health and charge of the battery (%)
- Adjustable brightness
- ✓ Automatic temperature compensation

Test of the starter and the alternator circuit

- ✓ Tests the starting voltage.
- ✓ Tests the no-load and charging voltage as well as the charging current ripple.



Its advantages

- 3 in 1 tester
- Extra-long cables (1,75m)
- Very good readibility (wide lighted screen)

Technical specifications

- ✓ 7 languages: French, English, German, Spanish, Italian, Portuguese, Japanese
- ✓ **ABS body** (acid proof)
- + anti-shock protection
- Power supply: 6 batteries of 1,5 Volt included (type LR6 AA)
- ✓ Temperature condition: 0°C to 50°C
- **Tolerance :** CCA < \pm 5% Voltage \pm 0,05%
- ✓ **Delivered ready for use:** 6 batteries, and protection case
- ✓ Cable length: 1,75 m
- ✓ Dimensions : 190 x 50 x 115
- Weight: 420 gr

