

365532
DIGITAL METERED CONTROL VALVE, EC30 SERIES, 30 L/MIN, FLEXIBLE OUTLET, AUTOMATIC


SAMOA metered control valves are used at the end of hose assembly for measured dispensing of lubricants and antifreeze solutions.

- Extensively and rigorously field tested. Reliable performance.
- High precision machined measuring chamber with tight tolerances, quality gears and stainless steel shafts eliminate the need of calibration to adjust for fluid viscosity.
- Sealed battery compartment and isolated electronic register for extended life.
- Easy to read large character display, with batch, trip (resettable totalizer) and totalizer functions.
- Rough TPE boot surrounds the entire meter for even greater durability.
- Replaceable AAA batteries.

DATOS TÉCNICOS

Accuracy	0.005
Fluid inlet	1/2" BSP (F)
Fluid outlet	1/2" BSP (F)
Fluids	Transmission fluid, Aceite, Coolant, Hydraulic oil, Gear oil
Maximum free flow delivery	30 l/min
Maximum free flow delivery (SI)	30 l/min, 8 gal/min
Maximum outlet pressure	100 bar (1450 psi)
Meter	Digital
Metric	Litres
Operating Temperature Range	-10 - 60 °C (14 - 140 °F)
Outlet nozzle type	Automatic
Weight	1.3 kg (2.8 lb)
Wetted materials	Acetal, TPU, Aluminium, Zinc plated steel, Stainless steel, NBR, Polyamide

DOCUMENTACIÓN

NOMBRE	DESCRIPCIÓN
836826.pdf	Instructions manual 2
836829.pdf	Instructions manual 1
836847.pdf	Instructions manual 3
836850.pdf	Instructions manual 3