



569006

**AUTOMATIC STAINLESS STEEL/POLYPROPYLENE NOZZLE
SPECIAL FOR PASSENGER CARS (MISS-FILLING
PREVENTION), 5 L/MIN, 1" BSP (M) INLET**



AdBlue/DEF nozzles with stainless steel and thermoplastic versions available. Depending on the model they can be manual or automatic, with spike or thread connection. 5 L/MIN, 1" BSP (M) inlet thread. Integrated mis-filling prevention (Elaflex).

DATOS TÉCNICOS

Accuracy	-
Fluid inlet	1" BSP (M)
Fluid outlet	-
Fluids	AdBlue/DEF
Maximum free flow delivery	10 l/min
Maximum free flow delivery (SI)	2.6 gal/min, 10 l/min
Maximum outlet pressure	3,5 bar (50 psi)
Meter	N/A
Metric	-
Operating Temperature Range	-5 - 55 °C (23 - 131 °F)
Outlet nozzle type	Miss-filling prevention
Weight	1.5 kg (3 lb)
Wetted materials	Stainless steel, Aluminium, NBR, Polyamide

CUADRO DE MODELOS

569005

Outlet nozzle type	N/A
--------------------	-----

569006

Outlet nozzle type	Miss-filling prevention
--------------------	-------------------------

