



413080

**CONTROL VALVE, PG-77/Z SERIES, 1 KG/MIN, GREASE,
RIGID OUTLET, Z-SWIVEL**



High pressure grease control guns with ergonomic body and trigger designed to reduce operator hand fatigue. Manufactured in aluminium with steel insert for high pressure. With z-swivel, rigid outlet and 3 jaw connector assembly

DATOS TÉCNICOS

| | |
|---------------------------------|---------------------------|
| Accuracy | - |
| Fluid inlet | 1/4" BSP (F) |
| Fluid outlet | 1/8" BSP (F) |
| Fluids | Grease |
| Maximum free flow delivery | 1 kg/min |
| Maximum free flow delivery (SI) | 1 kg/min, 2.2 lb/min |
| Maximum outlet pressure | 500 bar (7250 psi) |
| Meter | N/A |
| Metric | - |
| Operating Temperature Range | -10 - 70 °C (14 - 160 °F) |
| Outlet nozzle type | Grease connector |
| Weight | 0.95 kg (2.09 lb) |
| Wetted materials | Steel, Zinc plated steel |

DOCUMENTACIÓN

| NOMBRE | DESCRIPCIÓN |
|------------|-----------------------|
| 841801.pdf | Instructions manual 1 |

