

**363053**
**HIGH FLOW CONTROL VALVE, PA70 SERIES, 70 L/MIN, 30° RIGID, SEMIAUTOMATIC, 3/4" BSP (F)**


SAMOA large delivery control valves are used at the end of hose assembly to dispense large volumes of lubricants and antifreeze solutions.

- Extensively and rigorously field tested. Reliable performance. Heavy Duty aluminium pressure cast body to withstand the toughest working conditions.
- High flow pressure balanced valve for comfortable use.
- Large port inlet swivel (1" and 3/4"). Inlet filter with large screen surface.
- Safety guard avoids accidental openings.
- Trigger can be locked open for dispensing large volumes.
- Outlets have 3/4" BSP (M) connection thread and use a bonded seal washer to assure a leak free operation.

**DATOS TÉCNICOS**

Accuracy	-
Fluid inlet	3/4" BSP (F)
Fluid outlet	3/4" BSP (F)
Fluids	Aceite, Hydraulic oil, Transmission fluid, Gear oil, Coolant
Maximum free flow delivery	90 l/min
Maximum free flow delivery (SI)	21.1 gal/min, 80 l/min
Maximum outlet pressure	100 bar (1450 psi)
Meter	N/A
Metric	-
Operating Temperature Range	-10 - 70 °C (14 - 160 °F)
Outlet nozzle type	Semiautomatic
Weight	2.05 kg (4.5 lb)
Wetted materials	Aluminium, Brass, Zinc plated steel, NBR

**DOCUMENTACIÓN**

NOMBRE	DESCRIPCIÓN
836837.pdf	Instructions manual 1